

Switching Mode Power Supply 24V/1A

[Model No: SMPS24-1A]



Features:

- . Latest Top Switch based design.
- . Maximum output power of 24W.
- . High efficiency, High reliability, Low cost.
- . AC input voltage range 180V ~ 265V AC.
- . Built-in EMI filter.
- . Low Ripple and Noise.
- . Soft start circuit to limit the AC inrush current.
- . Compact, Light weight.
- . Momentary output short circuit Protection, Over load protection.
- . 100% Full load burn-in test.

Specifications:

. Input Characteristics:

Input Voltage	180V – 265 VAC
Input Frequency	50 Hz.
Input Connector	3 Core cable I/P.
Indications	
Input Protections	a) 3 Amp, 20mm fast blow, Glass fuse. b) MOV for input over voltage protection.
Filters	EMI/RFI.

. Output Characteristics:

Output Voltage	24 VDC
Output Current	1 A
Output Power	24 W
Output Connector	2 Core cable o/p.
Output Indications	a) Output Ok – Red color LED.
Output Protections	Over Load Protection
Line Regulation	< + / - 0.5%
Load Regulation	< + / - 0.5%
Ripple and Noise	< + / - 1% P-P.

. Environmental Characteristics:

Operating Temperature	55 C at Full Load and 70 C at 60% load.
Cooling	By free air convection
Relative Humidity	95% NC.

. General Characteristics:

Efficiency	70%
Hold Time	> 20mSec on full load.
Dimension (L X H X D) mm	(131 X 96 X 50)
Mounting	Wall Mounting

Note:

- 1) All these parameters are specified at 230V AC input.
- 2) For continuous improvement, specifications are subject to change.