

## **DROPBOLT** **MODEL IDB-20**



### **SPECIFICATIONS: UL/CE**

<b>OPERATING MODE</b>	<b>FAILSAFE (Power to close)</b>
<b>OPERATING VOLTAGE</b>	<b>+12VDC</b>
<b>STARTING CURRENT</b>	<b>900mA</b>
<b>STANDBY CURRENT</b>	<b>150mA</b>
<b>SOLID BOLT</b>	<b>POLISHING HOUSING,800KG HOLDING FORCE</b>
<b>SUITABLE FOR</b>	<b>WOODEN DOOR, GLASS DOOR, METAL DOOR.</b>
<b>AUTOLOCK TIMEDELAY</b>	<b>0, 3, 6,9 SEC.</b>
<b>SIGNAL OUTPUT</b>	<b>DOOR STATUS OUTPUT,COM/NO/NC</b>
<b>SURFACE TEMPERATURE</b>	<b>LOW TEMPERATURE</b>
<b>INDUCTION DISTANCE</b>	<b>8mm.</b>
<b>SPECIAL DESIGNED</b>	<b>TESTED TO 500000CYCLES</b>
<b>FACEPLATE MATERIAL</b>	<b>HIGH ALUMINUM,CARRULOUSLINE FINISHED</b>
<b>FACEPLATE DIMENSIONS</b>	<b>(205LX35WX40H)mm.</b>
<b>BOLT DIMENSIONS</b>	<b>15mmDIA, STAINLESSSTEEL15mmTHROW</b>
<b>WEIGHT</b>	<b>0.7KG</b>

