

INTERLOCKING SYSTEM (NC) [MODEL : IIL-3CP-NC]



SPECIFICATIONS:

1. Operating Voltage : 230V AC, 50HZ.
2. Maximum 3 doors possible.
3. Sensor : Magnetic reed sensor (NC type).
4. Doors Status will be indicated on LED display with pulsed alarm.
5. Display module can be connected up to 8 numbers
6. Magnetic Reed sensor input wire should not exceed more than 100 meters in length.
7. Emergency alarm o/p should not exceed 12V/0.5A rating.
8. Box Dimensions (188L x 255H x 95D)mm.

FEATURES :

1. Flexible interfacing through access control panel.
2. Independent door control output relay.
3. Door status alarm with time control. And LED o/p.
4. Emergency exit with alarm provision.


INSTALLATION INSTRUCTIONS :

- LED indicator should be connected in parallel.
- NC type Magnetic contact sensor must be used.
- Exit switch should be mounted on the inner side of the door to exit
- All negative (or) ground can be connected in common.
- This interlocking module can be used maximum up to 3 doors.
- Entry/Exit, switch and Magnetic contact sensor should be connected in series.
- Good quality cable must be used.
- Emergency alarm o/p should not exceed 12V/0.5A

APPLICATIONS:

It is used in Chemical industry, Pharmaceutical industry and hazardous Area.

WIRING DIAGRAM :



JORDAN SAFETY SYSTEMS. AN ISO 9001:2000 CERTIFIED COMPANY